

SCV-F Data Sheet





Compact 18" sensor controlled subwoofer, Extended frequency range down to 25 Hz (-6 dB)

The CODA Audio award winning sensor controlled technology is extended with the compact SCV-F subwoofer. Combining a closed feedback-loop control with large, low noise laminar flow ports the SCV-F subwoofer offers increased output and well controlled response.

SCV-F Features

- Ompact 18" sensor controlled subwoofer
- ♠ Extended frequency range down to 25 Hz (-6 dB)
- The feedback loop control ensures extreme fast transient response and ultra low distortion
- Flyable or ground stackable in cardio or omni configurations
- Rigging is compatible to AiRAY and VIRAY


- Subwoofer arrays can be curved for perfect time alignment with AiRAY and ViRAY
- LINUS14/14D and LINUS10 DSP-amplifier and comparator provides integrated power and feedback loop control solution





SCV-F Data Sheet


Product Type	Sensor controlled sub
Dimensions (WxHxD):	674 x 490 x 790 mm / 26.54 x 19.29 x 31.1"
Dimensions Including Hardware (WxHxD):	674 x 495 x 806.5 mm / 26.54 x 19.49 x 31.75"
Net Weight	57 kg / 125.66 lb
Frequency Response	25 Hz - 150 Hz (-6 dB)
Power handling AES / peak (passive):	1500 W / 6000 W
- Low AES / peak:	N/A
- Mid / High AES / peak:	N/A
Max. peak SPL (with LINUS10):*	138 dB
Dispersion Horizontal:	N/A
Dispersion Vertical:	N/A
Components Low frequency:	18" Nd ultra low distortion woofer, 4" (101.6 mm) VC, 1500 W (AES) each
Components Mid/High frequency:	N/A
Crossover point:	N/A
Input Connectors:	2x Neutrik™NL4MP (rear) +1 x Neutrik™NL4MP (front)
Nominal impedance LF / MF+HF:	8 Ω (+1/-1)
Enclosure material:	Birch plywood
Suspension	Flying hardware Integrated Allows curving (0°, 2.5°, 5°)

^{*}Measured with pink noice 6 dB crest factor. Half-space loading.









Other SCV-F System Products



ViRAY
Compact, 3-Way Symmetrical
Line Array System



SC2-F Sensor Controlled Bass Extension



LINUS14/14D 4-Channel Loudspeaker

4-Channel Loudspeaker Management Amplifier

CODA AUDIO GmbH

Boulevard der EU 6, 30539 Hannover, Expo Park, Germany E-Mail: contact@codaaudio.com Website: www.codaaudio.com



